


38207N1
2-in-1 sensor faucet




Technical Specifications:

Suite:	KLUDI-WAVE
Flow Rate:	3.9L/min at 3 bar
Power supply:	AC100-240V
Color:	Brushed Bronze
Max protect run time:	60 seconds
Aerator:	Neoperl
Dimensions:	234mm (L)
Capacity:	3000ml

Code:	Name:
38207N1	KLUDI-WAVE 2-in-1 AUTO SENSOR FAUCET WITH SOAP DISPENSER - WALL MOUNTED laser sensor activation blue and red LED light display The left sensor is for water and the right sensor is for soap electric power supply AC100-240V Water pressure 0.05 MPa – 0.80 MPa G½" inlet thread 3000ml bottle capacity, output volume 0.6-2.0ml/cycle Suitable soap viscosity, Liquid: 100-3500cps Suitable soap PH 5-9 Certified to BS EN 15091:2013 standard

Water Flow Rate #:



variation: ± 15%

Dimensions: All dimensions in mm. Tolerance of vitreous china & fireclay items: ± 5% for below 200mm and ± 3% for above 200mm; for all other items tolerance ± 1%. Note: Due to a continuing development program to improve design and performance, the manufacturer reserves all rights to vary specifications without prior information. Please note accessories are for photographic use only.